

Product datasheet

Specifications



Galaxy VS UPS 15kW 400V, 1 internal 9Ah smart modular battery string, expandable to 4, Start-up 5x8

GVSUPS15KB4HS

Overview

Presentation Highly efficient, easy-to-deploy 15kW, 400V 3-phase UPS that brings best-in-class power protection and low total cost of ownership to edge, small and medium data centers, as well as to critical infrastructure in commercial and industrial applications. Includes 5x8 start-up service and 1 smart high-capacity modular battery string, expandable to 4 strings for extended runtime. Runtime charts available in the Documents tab.

Lead time

Main

Main Input Voltage	400 V 3 phases
Other Input Voltage	380 V 415 V
Main Output Voltage	400 V 3 phases
Other Output Voltage	380 V 415 V
Rated power in W	15 kW
Rated power in VA	15 kVA
Output connector type	Hard wire 5-wire (3P + N + E) 1
Battery type	Internal modular battery VRLA
Provided equipment	Battery modules ship installed Dust filter EcoStruxure IT ready (UPS) Installation guide Integrated network management Power modules ship installed Start-up service

General

Bypass voltage tolerance	+/- 10 %
Redundant	No

Physical

Colour	White
Height	148.5 cm
Width	52.1 cm
Depth	84.7 cm
Net weight	320 kg

USB compatible	No
----------------	----

Input

Network frequency	40...70 Hz
Number of input connectors	1 hard wire 5-wire (3P + N + E) 1 hard wire 3-wire (1P + N + E)
Input voltage limits	340...460 V 400 V
Maximum input current	27 A
Max short time withstand current	65 kA
Input harmonic distortion	Less than 3 % for full load
Load power factor	From 0.7 leading to 0.7 lagging without any derating
Input Power Factor at Full Load	0.99

Output

Maximum configurable power in W	15 kW
Harmonic distortion	Less than 3 %
Output frequency	50 Hz sync to mains 60 Hz sync to mains 50 Hz +/- 0.1 % for 50 Hz nominal unsynchronised 60 Hz +/- 0.1 % for 60 Hz nominal unsynchronised
Crest factor	2.5
Wave type	Sine wave
Output voltage tolerance	+/-1% after 50ms
Output harmonic distortion	< 1% linear load and < 3% non-linear load
Output overload operation	10 minutes at 125% and 60 seconds at 150%
Bypass type	Built-in static bypass
Maximum configurable power in VA	15 kVA

Conformance

Product certifications	UL 1778 5th edition
Standards	CSA C22.2 No 107.3 EN/IEC 62040-1 EN/IEC 62040-2 EN/IEC 62040-3 IEC 60721-4-2 level 2M2

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...3281 ft
Ambient air temperature for storage	-15...40 °C
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0.00...3048.00 m
Acoustic level	55 dBA
Heat dissipation	1763 Btu/h
IP degree of protection	IP20

Batteries & Runtime

Battery voltage	480 V
Discharge battery voltage	384 V DC
Max current discharge	41 A
Battery power in VAH	0 VAh runtime
Extended runtime	0

Communications & Management

Free slots	1
Control panel	Touch screen LCD user interface
Alarm	Audible and visible alarms prioritized by severity

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	168 cm
Package 1 Width	99 cm
Package 1 Length	64 cm
Package 1 Weight	360 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	1 year repair or replace
----------	--------------------------

Recommended replacement(s)